

PAC-42H

PAC-170

4-slot Half-size Industrial PC Chassis

7-slot Full-size Industrial PC Chassis



PAC-42H



PAC-170

SPECIFICATIONS

- Drive Bays : 1 x 3.5" FDD; 1 x 3.5" or 2.5" HDD
- One 8cm cooling fan with removable filter
- Designed with fan fault detecting system
- Supports backplane : BP-4S, IP-4S, IP-4S2
- Supports power supply : ACE-870 series and ACE-865V
- Vibration : 5~17Hz, 0.1" double amplitude displacement
17~640Hz, 1.5G acceleration peak to peak
- Shock : 10G acceleration peak to peak (11ms)
- Colors : White (PANTONE 413C)
- Dimensions : 140(W) x 230(H) x 256.6(D)mm; (5.5" x 9" x 10.1")
- Net/GW : 4/6 (kg)

ORDERING INFORMATION

- PAC-42HW/ACE-870A/B : 4-slot compact chassis with ACE-870A power supply & B backplane

SPECIFICATIONS

- AT KBD connector on front panel
- Front panel made by plastic
- Drive Bays : 1 x 3.5" FDD; 1 x 5.25" Drive; 2 x 3.5" HDD
- One 8cm cooling fan with removable filter
- Supports backplane : BP-7S, IP-7S, PCI-7S, PCIAGP-6S
- Supports power supply : PS/2 size AT/ATX power supply (ACE-93x/92x/916 series and ACE-828 series)
- Vibration : 5~17Hz, 0.1" double amplitude displacement
17~640Hz, 1.5G acceleration peak to peak
- Shock : 10G acceleration peak to peak (11ms)
- Color : Industrial Green (PANTONE 417C)
- Dimensions : 193(W) x 254(H) x 432(D)mm; (7.6" x 10" x 17")
- Net/GW : 8/10 (kg)

ORDERING INFORMATION

- PAC-170G/ACE- : 7-slot compact chassis with ACE- power supply
- Power Supply
- Standard Version :
- PAC-170G/ACE-925A : 7-slot compact chassis with ACE-925A power supply

PAC-70AH 7-slot Half-size Industrial PC Chassis

PAC-75H 7-slot Half-size Industrial PC Chassis



PAC-70AH



PAC-75H

SPECIFICATIONS

- Drive Bays : — 1 x 3.5" FDD
— 1 x 3.5" HDD
- One hot-removable 8cm cooling fan with filter
- Designed with fan fault detecting system
- Supports backplane : BP-7S, IP-7S
- Supports power supply : PS/2 size AT/ATX power supply (ACE-93x/92x/916 series and ACE-828 series)
- Vibration : 5~17Hz, 0.1" double amplitude displacement
17~640Hz, 1.5G acceleration peak to peak
- Shock : 10G acceleration peak to peak (11ms)
- Color : White (PANTONE 413C)
- Dimensions : 321(W) x 175.5(H) x 280.6(D)mm; (12.6"x6.9"x11")
- Net/GW : 7/10 (kg)

ORDERING INFORMATION

- PAC-70AHW/ACE-920A:
7-slot compact chassis with ACE-920A power supply

ORDERING INFORMATION

- Front panel with lockable door to protecting the system safety
- Drive Bays : — 1 x 3.5" FDD
— 1 x 5.25" Drive
— 1 x 3.5" HDD
- One hot-removable 8cm cooling fan with filter
- Designed with fan fault detecting system
- Supports backplane : BP-7S or IP-7S
- Supports power supply : ACE-890 series power supply
- Vibration : 5~17Hz, 0.1" double amplitude displacement
17~640Hz, 1.5G acceleration peak to peak
- Shock : 10G acceleration peak to peak (11ms)
- Color : White (PANTONE 413C)
- Dimensions : 321(W) x 175.5(H) x 280.6(D)mm; (12.6"x6.9"x11")
- Net/GW : 7/9 (kg)

ORDERING INFORMATION

- PAC-75HW/ACE-890A:
7-slot compact chassis with ACE-890A power supply