

PAC-53H

PAC-42F

3-slot Half-size Industrial PC Chassis

4-slot Full-size Industrial PC Chassis



PAC-53H



2.5" HDD



PAC-42F

SPECIFICATIONS

- **Drive Bays:** -2 x 2.5" HDD
- **Supports backplane:** IP-3S, IP-3S2, BP-3S
- **Supports power supply:** ACE-870 series or ACE-865V
- **Vibration:** 5~17Hz, 0.1" double amplitude displacement
17~640Hz, 1.5G acceleration peak to peak
- **Shock:** 10G acceleration peak to peak (11ms)
- **Colors:** White (PANTONE 413C)
- **Dimensions:** 90(W) x 200(H) x 214.6(D)mm; (3.5" x 7.9" x 8.4")
- **Net/GW:** 3/4 (kg)

ORDERING INFORMATION

- **PAC-53HW/ACE-870A/B:**
3-slot compact chassis with ACE-870A power supply & B backplane

SPECIFICATIONS

- **Drive Bays:** — 1 x 3.5" FDD — 2 x 3.5" HDD
- **One 8cm cooling fan with removable filter**
- **Designed with fan fault detecting system**
- **Supports backplane:** BP-4S, IP-4S, PCI-4S
- **Supports power supply:** ACE-890 Series power supply
- **Vibration:** 5~17Hz, 0.1" double amplitude displacement
17~640Hz, 1.5G acceleration peak to peak
- **Shock:** 10G acceleration peak to peak (11ms)
- **Color:** White (PANTONE 413C)
- **Dimensions:** 140(W) x 200(H) x 396(D)mm; (5.5" x 7.9" x 15.6")
- **Net/GW:** 5/7 (kg)

ORDERING INFORMATION

- **PAC-42FW/ACE-890A** 4-slot compact chassis with ACE-890A power supply


PAC-100A/120A 6/10-slot Full-size Industrial PC Chassis

PAC-125 10-slot Full-size Industrial PC Chassis



Wall-Mount
Mounting Kit

PAC-100A



Wall-Mount
Mounting Kit

PAC-120A



PAC-125W



The Internal
Configuration!

SPECIFICATIONS

- **Front panel made by plastic**
- **AT type KBD connector on front panel with cap protection**
- **Drive Bays:**

Model	3.5" FDD	3.5" HDD
PAC-100A	2	1
PAC-120A	2	1

- One 8cm cooling fan with removable filter
- Designed with anti-vibration card clamp to keep system stable
- **Supports backplane:** — PAC-100A : BP-6S, IP-6S, PCI-6S, PCIAGP-5S
— PAC-120A : BP-10S, IP-10S, PCI-10S, PCI-10S2, PCIAGP-9S2, PXAGP-9S
- **Supports power supply:** PS/2 size AT/ATX power supply (ACE-93x/92x/916 series and ACE-828 series)
- **Vibration:** 5~17Hz, 0.1" double amplitude displacement
17~640Hz, 1.5G acceleration peak to peak
- **Shock:** 10G acceleration peak to peak (11ms)
- **Color:** Industrial Green (PANTONE 417C)
- **Dimensions:** — PAC-100A : 232(W) x 175(H) x 419(D)mm; (9.1"x6.9"x16.5")
— PAC-120A : 321(W) x 175(H) x 419(D)mm; (12.6"x6.9"x16.5")
- **Net/GW (kg):** 7/9(PAC-100A), 8/11(PAC-120A)

ORDERING INFORMATION

- **PAC-100AG/ACE-920A** : 6-slot compact chassis with ACE-920A power supply
- **PAC-120AG/ACE-920A** : 10-slot compact chassis with ACE-920A power supply
- **PAC-120AGM/ACE-920A** : AT MB compact chassis with ACE-920A power supply

ORDERING INFORMATION

- **Front panel with lockable door to protect the system**
- **Drive Bays:** — 1 x 3.5" FDD
— 1x 5.25" Drive
— 1 x 3.5" HDD
- **One hot-removable 8cm cooling fan with filter**
- **Designed with fan fault detecting system**
- **Designed with anti-vibration card clamp to keep system stable**
- **Supports baby AT form factor PC motherboard**
- **Supports backplane:** BP-10S, BP-10SD, IP-10S, PCI-10S, PCIAGP-9S2, PXAGP-9S
- **Supports power supply:** PS/2 size AT/ATX power supply (ACE-93x/92x/916 series and ACE-828 series)
- **Vibration:** 5~17Hz, 0.1" double amplitude displacement
7~640Hz, 1.5G acceleration peak to peak
- **Shock:** 10G acceleration peak to peak (11ms)
- **Color:** White (PANTONE 413C)
- **Dimensions:** 320(W) x 175(H) x 419(D)mm; (12.6" x 6.9" x 16.5")
- **Net/GW:** 9/13 (kg)

ORDERING INFORMATION

- **PAC-125W/ACE-920A** :
10-slot compact chassis with ACE-920A power supply