

PR-1300/1500

3, 5-slot Half-size Chassis



PR-1300 Top View



PR-1500 Top View

SPECIFICATIONS

- **Drive Bays :**
PR-1300: 1 x 3.5" FDD
PR-1500: 1 x 3.5" FDD, 1 x 3.5" HDD
- **One 8cm fan with filter (PR-1500), 6cm fan with filter (PR-1300)**
- **Vibration :** 5-17Hz, 0.1" double amplitude displacement
17-640Hz, 1.5G acceleration peak to peak
- **Shock :** 10G acceleration peak to peak (11ms)
- **Colors:** White (Pantone 413C)
- **Support Backplane:**
PR-1300: BP-3S with ACE-916A AT power supply
IP-3SA with ACE-816A ATX power supply
PR-1500: BP-5S with ACE-916A AT power supply
IP-5SA with ACE-816A ATX power supply
- **Power Supply:**
Standard equipped with ACE-816A 150W ATX power supply
Also support ACE-916A 150W AT power supply
- **Dimensions:** PR-1300: 266(W) x 88(H) x 254(D)mm
PR-1500: 266(W) x 132(H) x 254(D)mm
- **Net/GW (kg):** 4/6(PR-1300), 4/7(PR-1500)

ORDERING INFORMATION

PR-No.	W / Backplane	Power Supply
1300	{ BP-3S or IP-3SA	ACE-916A or ACE-816A
1500	{ BP-5S or IP-5SA	

PR-103/105 3, 5-slot Half-size Industrial PC Chassis

PAC-50/51/52 3, 4, 6-slot Half-size Industrial PC Chassis


PR-103




PR-105



PAC-50



PAC-51



PAC-52

SPECIFICATIONS

- **Supports backplane :**
— PAC-50 : IP-3S, BP-3S, IP-3S2
— PAC-51 : IP-4S, BP-4S, IP-4S2
— PAC-52 : IP-6S, BP-6S
- **Supports max. card length : 190mm**
- **Five DC input terminal block for power supply connection**
- **Convenient FDD, HDD & parallel port cables for external connection**
- **Vibration :**
— 5~17Hz, 0.1" double amplitude displacement
— 17~640Hz, 1.5G acceleration peak to peak
- **Shock :**
10G acceleration peak to peak (11ms)
- **Color :**
Industrial Green (PANTONE 417C)
- **Dimensions :**
— PAC-50 :
91(W) x 146.7(H) x 218(D)mm;
(3.6" x 5.7" x 8.6")
— PAC-51 :
114(W) x 146.7(H) x 218(D)mm;
(4.5" x 5.7" x 8.6")
— PAC-52 :
152(W) x 146.7(H) x 218(D)mm;
(6" x 5.7" x 8.6")
- **Net/GW (kg) :** 2/3 (PAC-50/51/52)

SPECIFICATIONS

- **Drive Bays :** — PR-103 : 1 x 3.5" FDD
— PR-105 : 2 x 3.5" FDD
- **One 8cm cooling fan with removable filter**
- **Supports backplane :** — PR-103 : BP-3S, IP-3S
— PR-105 : BP-5S, IP-5S
- **Supports power supply :** ACE-870 series or ACE-865V
- **Ship with a mounting kit for Rack mounting solution**
- **Vibration :** 5~17Hz, 0.1" double amplitude displacement
17~640Hz, 1.5G acceleration peak to peak
- **Shock :** 10G acceleration peak to peak (11ms)
- **Colors :** White (PANTONE 413C)
- **Dimensions :**
— PR-103 : 266(W) x 88(H) x 254(D)mm; (10.5" x 3.5" x 10")
— PR-105 : 266(W) x 132(H) x 254(D)mm; (10.5" x 5.2" x 10")
- **Net/GW (kg) :** 3/6(PR-103), 4/6(PR-105)

ORDERING INFORMATION

- **PR-103W/ACE-[P] :** 3-slot compact chassis with ACE-[P] power supply
- **PR-105W/ACE-[P] :** 5-slot compact chassis with ACE-[P] power supply
- **Power Supply**
- **Standard Version :**
- **PR-103W/ACE-870A :** 3-slot compact chassis with ACE-870A power supply
- **PR-105W/ACE-870A :** 5-slot compact chassis with ACE-870A power supply

ORDERING INFORMATION

- **PAC-50G/[B] :** 3-slot compact chassis with [B] backplane
- **PAC-51G/[B] :** 4-slot compact chassis with [B] backplane
- **PAC-52G/[B] :** 6-slot compact chassis with [B] backplane
- **Backplane**
(Please select specified backplane for each PAC-50/51/52 chassis)