

RACK-810/814 RACK-3025A

10/14-Slot full size industrial chassis

4U Height 10-Slot Full Size Industrial PC Chassis
With Redundant Power Supply Case



USB port

RACK-810



RACK-814



Top View

Micro ATX
Mother Board
Version Available

RACK-3025AW



RACK-3025AB

ACE-RC02
Dual Redundant
Power Supply
Case

Dual Redundant
Power Supply !



Specifications

- 4U height 19" Rack mounting chassis
- Front panel with lockable door to protect the running system
- Bracket area is located in the front for easy access to the cables
- One USB port on front panel
- Drive Bays:
 - RACK-810: — 2 x 5.25 Drive, 1 x 3.5 FDD/HDD Drive
 - RACK-814: — 1 x 3.5" FDD, 1 x 5.25" Drive, 1 x 3.5" HDD
- Three hot-removable 8cm cooling fans
- Designed with anti-vibration card clamp to keep system stable
- Supports ATX form factor PC motherboard(RACK-814)
- Supports backplane :
 - RACK-810: BP-10S,BP-10SD,PCI-10S,PX-10S,IP-10S,IPX-9S, IPX-9S,PCIAG-9S2,PXAGP-9S
 - RACK-814: BP-14S,BP-14SD,PCI-13SD,PCI-14S,PCI-14S2, PCI-14S3, PX-14S5,IP-13SD,IP-14S,IPX-13S, PCIAGP-13S2,PCIAGP-13S3,PXAGP-12S2, PXAGP-13S,PXAGP-13S3
- Supports power supply: PS/2 size AT/ATX PSU (ACE-93x/92x/916 series and ACE-828 series) or ACE-C232 mini redundant UPS
- Optional rack-mount slide: 24" or 18"
- Vibration: 5~17Hz, 0.1" double amplitude displacement 17~640Hz, 1.5G acceleration peak to peak
- Shock: 10G acceleration peak to peak (11ms)
- Colors: Black (PANTONE Black C) or White (PANTONE 413C)
- Dimensions: 431(W) x 176(H) x 465.4(D)mm; (17" x 6.9" x 18.3")
- Net/GW (kg): 13/18

Ordering Information:

- RACK-814 **C**/ACE-925A : 4U 14-slot rackmount chassis with ACE-925A power supply
- RACK-814 **C**/ATX/ACE-828A : 4U ATX MB rackmount chassis with ACE-828A power supply
- RACK-814 **C**/R/ACE-C232 : 4U 14-slot rackmount chassis with ACE-C232 redundant power supply
- RACK-810 **C**/ACE-832A : 4U 10-slot rackmount chassis with ACE-832A Power supply
- C** Color Code : B = Black, W = White **P** Power Supply
- SLIDE-18: 18" rack-mount slide
- SLIDE-24: 24" rack-mount slide
- EXTENDER-6: 6" extender for 18" or 24" slide

Specifications

- 4U height 19" Rack mounting chassis
- Front panel with lockable door to protect the running system
- Two reset switches for dual system applications
- AT type KBD connector on front panel
- Drive Bays: — 1 x 3.5" FDD — 3 x 5.25" Drive
- Two 8cm cooling fans with removable filter
- Designed with anti-vibration card clamp to keep system stable
- Supports backplane: BP-10S, BP-10SD, PCI-10S, IP-10S, PCIAGP-9S2,PXAGP-9S
- Supports 10 full size cards
- Built-in ACE-RC02 redundant power case
- Supports power supply: ACE-R20 series redundant power module
- Optional rack-mount slide : 24"
- Vibration: 5~17Hz, 0.1" double amplitude displacement 17~640Hz, 1.5G acceleration peak to peak
- Shock: 10G acceleration peak to peak (11ms)
- Colors: Black (PANTONE Black C) or White (PANTONE 413C)
- Dimensions: 431(W) x 176(H) x 511(D)mm; (17" x 6.9" x 20.1")
- Net/GW (kg): 17/22

Ordering Information:

- RACK-3025A **C** **M** : 4U AT MB rackmount chassis with ACE-RC02 power supply case
- RACK-3025A **C** : 4U 10-slot rackmount chassis with ACE-RC02 power supply case
- C** Color Code : B = Black; W = White
- ACE-R20A: AC input redundant power module for RACK-3025A
- ACE-R20T: 48V DC input redundant power module for RACK-3025A
- ACE-R20C: 24V DC input redundant power module for RACK-3025A (Please select one or two ACE-R20 series power module for each RACK-3025A chassis)
- SLIDE-24: 24" rack-mount slide
- EXTENDER-6: 6" extender for 18" or 24" slide